


# Traceable Micro Fiber Optic Cable (Gel-Filled)

2F~432F, Single-Mode, Colored Fiber, Loose Tube, Indoor/Outdoor, PE Jacket

## Cross Sectional Diagram



## Applications

- Local area networks
- Suitable for underground duct installation
- Suitable for installation in limited environment

## Features

- Small size & light weight for limited conduit space
- Reduces cable preparation and installation time
- PE Jacket

## Specifications

Mechanical Specifications									
Fiber Count	2	12	24	48	72	96	144	288	432
Fibers per Tube	2	12	12	12	12	12	12	12	24
Outer Diameter [mm (in)]	5.5 (0.21)	5.5 (0.21)	5.5 (0.21)	5.5 (0.21)	5.5 (0.21)	6.3 (0.24)	8.1 (0.32)	9.7 (0.38)	11.1 (0.43)
Weight [kg/km (lb/1000 ft)]	21.2 (14.2)	21.6 (14.5)	22.1 (14.8)	23.2 (15.5)	24.4 (16.3)	32.4 (21.7)	58.2 (39.1)	80.5 (54.0)	100.9 (67.8)
Max. Tensile Strength, Short-term / Long-term	890 N / 260 N (200 lbf / 58 lbf)					1200 N / 420 N (270 lbf / 94 lbf)			
Crush Resistance	500 N / 100 mm								
Min. Bend Radius- Installation	20 times x cable O.D.								
Min. Bend Radius- Operation	10 times x cable O.D.								

Spec. No: V02MFGCX2CGHPBK24KD



### General Specifications

Fiber Coating	Colored
Fiber Type	Single-Mode (OS2)
Tube Type	Gel-filled
Tube Material	PBTP (Polybutylene Terephthalate)
Strength Member	FRP (Fiber Reinforced Plastic)
Tracer wire	24AWG Cu wire
Outer Jacket Material	PE (Polyethylene)
Outer Jacket Color	Black

### Fiber & Tube Coloring

1	2	3	4	5	6	7	8	9	10	11	12
Blue	Orange	Green	Brown	Slate	White	Red	Black	Yellow	Violet	Pink	Aqua
13	14	15	16	17	18	19	20	21	22	23	24
Blue*	Orange*	Green*	Brown*	Slate*	White*	Red*	Black*	Yellow*	Violet*	Pink*	Aqua*

\*With one black stripe (black fiber & tube will have a natural stripe)

### Environmental Conditions

Temperature Range – Installation	- 10°C to + 40°C ( 14°F to 104°F)
Temperature Range - Storage	- 40°C to + 70°C (- 40°F to 158°F)
Temperature Range - Operation	- 40°C to + 70°C (- 40°F to 158°F)

### Optical Characteristics (Single-Mode)

Fiber Category	OS2 (G652D, G657A1)		
Max. Attenuation	0.36 dB/km	0.36 dB/km	0.25 dB/km
Wavelengths	1310 nm	1383 nm	1550 nm

\*The values of fiber attenuation loss change are the results measured after all tests have been completed



**Seoul Office** | Zip code 06525

5F, Lasung Bldg., 59, Naruteo-ro, Seocho-gu, Seoul, Korea

**Iksan Factory** | Zip code 54528

18, Samginonggongdanji-gil, Samgi-myeon, Iksan-si, Jellabuk-do, Korea

Tel: +82-2-707-0230 | Fax: +82-2-707-0232 | [www.hscnci.com](http://www.hscnci.com)

Spec. No: V02MFGCX2CGHPBK24KD